C7735 Return Air Sensor

Mount on return duct for backup control of non-zoned RedLINK™ enabled wireless systems. Works with the EIM to maintain safe indoor temperatures if power is lost at the wireless thermostat.

- Works with THM5320R1000 Equipment Interface Module to maintain safe indoor temperatures if power is lost at the wireless thermostat
- Takes control of the equipment by turning on the blower fan and sensing the indoor temperature of the home
- Controls heating at 62 F and cooling at 82 F
- Provides homeowners with peace of mind
- Installs in minutes
- Includes mounting hardware

Application: Mount on return duct for backup control of non-zoned systems
Dimensions, Approximate: 3 7/8 in. high x 4 1/8 in. wide x 1 1/4 in. deep (77 mm x 102 mm x 25 mm). Sensor probe: 3 3/4 in. long (77 mm)

Color: Gray
Operating Temperature Range: 0 F to 200 F (-17.8 C to 93.3 C)
Mounting: Mounts on return duct

Product Number	Comments	Used With
C7735A1000/U	Return Air Sensor is also available in kits for non-zoned systems	THM5320R1000 Equipment Interface Module; TH6320R1004 or TH5320R1002 Wireless FocusPRO® Thermostat

C7089 Outdoor Sensor

Remote outdoor temperature sensor, when installed, the current outdoor temperature is displayed. Also can be used to manage dual fuel and lock-out expensive auxiliary heat in heat pump applications.

- Mounting clip allows easy sensor positioning on siding or soffit
- Includes 60 in. leadwires
- Factory calibrated; no field calibration required
- Maximum wire run of 200 feet

Dimensions, Approximate: 2 1/4 in. x 3/8 in. with 60 in. leadwires (57 mm x 10 mm with 1524 mm leadwires.)
Operating Humidity Range (% RH): 5 to 95% RH, non-condensing

Ambient Temperature Range: -40 F to +128 F (-40 C to +53 C)
Mounting: Mounting Clip provided and screws provided.

Product Number	Description	Application	Used With
C7089B1000/U	Outdoor sensor used to measure outdoor temperature	Outdoor sensor for Chronotherm IV thermostats and TZ-4 Zone Panel	TZ-4 Zone Panel
C7089U1006/U	Outdoor Sensor used to measure the outdoor temperature	Outdoor sensor for Prestige® IAQ, VisionPRO with RedLINK™ and VisionPRO IAQ Thermostats	Prestige® IAQ, VisionPRO® Series Thermostats, VisionPRO® IAQ Thermostat

C7189 Remote Indoor Sensor

The Remote Indoor Temperature Sensor is used to sense temperature remotely.

- Used to sense temperature if the thermostat is installed in a poor temperature sensing location.
- Small remote temperature sensor to match any room decor.
- Easy to install and use.
- Factory calibrated; no field calibration required.
- Works with a maximum 200 foot wire run.

Application: Remote Indoor Temperature Sensor for Prestige® IAQ, VisionPRO and VisionPRO IAQ Thermostats
Dimensions, Approximate: 1 1/2 in. wide x 2 1/4 in. high x 3/4 in. deep (38 mm x 57 mm x 19 mm)
Color: Premier White®
Operating Humidity Range (% RH): 5 to 95% RH, non-condensing
Ambient Temperature Range: 45 F to 88 F (7 C to 32 C)
Mounting: Mounts directly on wall using mounting screws and anchors provided

	Product Number	Description	Temperature Setting Range	Used With
*	**C7189U1005/U**	Remote indoor sensor for remote sensing applications	See Thermostats	Prestige IAQ®, VisionPRO® and VisionPRO® IAQ Series Thermostats

** TRADELINE models • SUPER TRADELINE models*